

DTOX Signature

SEMI SYNTHETIC

SAE 10W-40 API SN/CF



recommends an **API SN** or earlier specification.



SYNTHETIC FORMULATION ENGINE OIL

DTOX Signature 10W-40 engine oil is specially formulated for all-year-round use. It features high-quality hydrocracked base oil and MoDTC friction modifier additive.

BENEFITS

- Excellent anti-wear and anti-friction
- Engine noise reduction
- Maintain performance under tough conditions
- Increase fuel efficiency
- Good cold start behaviour

CERTIFICATE OF ANALYSIS (COA):

PARAMETERS	METHOD	UNIT	SPECIFICATION	RESULT
Density @ 15°C	ASTM D4052	kg/l	Report	0.87
Flash Point (COC)	ASTM D92	°C	Min. 190	230
Ash (sulfated)	ASTM D874	mass %	-	1
Kinematic Viscosity @ 40°C	ASTM D445	mm ² /s	Report	88.70
Kinematic Viscosity @ 100°C	ASTM D445	mm ² /s	Report	13.20
Viscosity Index	ASTM D2270	-	Min. 130	150
HT-HS Viscosity @ 150°C	ASTM D4683	mPa.s	-	3.6
Pour Point	ASTM D97	°C	Max. -29.2	-32